Declaration of Performance

No: CE-DOP-19



REISSER° Ltd Bramhall Moor Technology Park, Pepper Road, Hazel Grove, Stockport SK7 5BW In accordance with the Construction Products Regulation, we of REISSER LTD hereby declare the;

REISSER® RETINOX Screws 4.5mm

Meets the requirements detailed in Annex ZA of the following harmonized standard;

BS EN14592:2008 + A1 2012 Timber structures - Dowel type fastener requirements

We declare that when used as intended the products named above comply with the relevant sections of the specification and all applicable requirements of the directives.

Dimensions:

Diamêter = 4.5mm Head Area = 55.1mm² Length = As stated on product

Material: 304 Unhardened

Corrosion protection:

SS 304 A2 Stainless Steel

Wax 1.3 (Service Class 3 according to EN1995-1-1)

Mechanical Strength & Stiffness:

Characteristic yield moment My = 3246 Nmm

Characteristic withdrawal resistance perpendicular to grain $f_{ax,90} = 17.6 \text{ N/mm}^2$ Timber density $\rho = 518 \text{kg/m}^3$ (Grade C16 @65%RH@20°C, Coating Class 1)

Head pull through resistance $f_{\text{head}} = 12 \text{ N/mm}^2$ Timber density $p = 650 \text{kg/m}^3$ (Grade 0SB3 @65%RH@20°C, Coating Class 1)

Tensile resistance (head pull off) $f_{tens} = 4.13 \text{kN}$

Torsional Ratio ≥ 1.5 = pass

The Initial type testing has been carried out to level 3 attestation by an independent notified body; **BM TRADA, NB # 1224** Chiltern House, Stocking Lane, Hughenden Valley, High Wycombe, HP14 4ND

And are controlled during manufacture by a FPC system that conforms to: ISO 9001: 2008

All declared performance data is as detailed on the summary sheets for each screw diameter and the full test reports.

These are available on request and can be viewed at www.reisser.co.uk and are contained in the relevant technical file that is monitored and maintained by an authorised person:

Patrick Meads of Reisser Ltd, Bramhall Tech Park, Pepper Road, Hazel Grove, Stockport, SK7 5BW

Signed for and on behalf of Reisser Ltd:

Patrick Meads day

JUIVE

2013

Director