

Nr.: DoP-9600-EN12209-EN.01

**1. Unique identification code of the product type:**

Mechanical lock according to EN 12209:2003/AC:2005

**2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4) of the CPR:**

Lock types 9602/08 FH, 9603/08 FH, 9604/08 FH

**3. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:**

Mechanical lock according to EN 12209:2003/AC:2005, suitable for use on fire/smoke resisting doors

**4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11 (5) of the CPR:**

ASSA ABLOY Nederland B.V.  
Postbus 40, 4940 AA Raamsdonksveer  
Meerval 3-5, 4941 SK Raamsdonksveer

**5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12 (2) of the CPR:**

N/A

**6. System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V:**

System 1 according to EN 12209:2003/AC:2005

**7. The product is covered by a harmonized standard:**

Notified Body	Harmonized standard	EC-Certificate of Conformity
SKG, Nieuwe Kanaal 9F, 6709 PA Wageningen Identifier: 0960	EN12209:2003 /AC:2005	0960-CPD- SKG.0116.3835.01.ENG

**7.1 The product is covered by other EC Directives:**

N/A

**8. European Technical Assessment:**

N/A

## 9. Declared Performance:

Classification key according to EN 12209:2003/AC:2005

Digit	1	2	3	4	5	6	7	8	9	10	11
Section	4.2.1	4.2.2	4.2.3	4.2.4	4.2.5	4.2.6	4.2.7	4.2.8	4.2.9	4.2.10	4.2.11
Grade (supported)	2	X	8	1	0	F	2	H	A	3	0

Dig.	Main features	Grade – Performance		
1	Category of use	Grade	Performance	
		1	For use by people with a high incentive to exercise care	
		2	For use by people with some incentive to exercise care	
		3	For use by the public where there is little incentive to exercise care	
2	Durability and load on latch bolt	Grade	Test cycles	Latch bolt load
		A	50.000	none
		B	100.000	none
		C	200.000	none
		F	50.000	10N
		G	100.000	10N
		H	200.000	10N
		L	100.000	25N
		M	200.000	25N
		R	100.000	50N
		S	200.000	50N
		W	100.000	120N
X	200.000	120N		
Y	200.000	250N		
3	Door mass and closing force	Grade	Door mass	Closing force
		1	≤ 100 kg	maximum 50N
		2	≤ 200kg	maximum 50N
		3	> 200kg or specified by the manufacturer	maximum 50N
		4	≤ 100 kg	maximum 25N
		5	≤ 200kg	maximum 25N
		6	> 200kg or specified by the manufacturer	maximum 25N
		7	≤ 100 kg	maximum 15N
		8	≤ 200kg	maximum 15N
		9	> 200kg or specified by the manufacturer	maximum 15N
4	Suitable for use on fire/smoke doors	Grade	Use	
		0	Not approved for use on fire/smoke resisting door assemblies	
		1	Suitable for use on fire/smoke resisting door assemblies	
5	Safety	No Safety requirement		
6	Corrosion resistance and temperature	Grade	Corrosion	Temperature
		0	none	none
		A	low resistance	none
		B	moderate resistance	none
		C	high resistance	none
		D	very high resistance	none
		E	moderate resistance	-20 °C to +80 °C
		F	high resistance	-20 °C to +80 °C
G	very high resistance	-20 °C to +80 °C		
7	Security and drill resistance	Grade	Performance	

		1 2 3 4 5 6 7	Minimum security, no drill resistance Low security, no drill resistance Medium security, no drill resistance High security, no drill resistance High security, with drill resistance Very high security, no drill resistance Very high security, with drill resistance			
8	Field of door application	Grade	Type	Application 1	Application 2	Application 3
		A B C D E F G H J K L M N P R	Mortice Mortice Mortice Rim Rim Rim Bored lock Mortice Rim Mortice Mortice Rim Rim Mortice Rim	Unrestricted Hinged door Sliding door Unrestricted Hinged door Sliding door Unrestricted Hinged door Hinged door Hinged door Sliding door Hinged door Sliding door Hinged door Hinged door		Supported Inwards
9	Key operation and locking	Grade	Key operation		Locking	
		0 A B C D E F G H	- Cylinder lock or latch Cylinder lock or latch Cylinder lock or latch Lever lock or latch Lever lock or latch Lever lock or latch Lock or latch without key operation Lock or latch without key operation		- Manually Automatically Manually with intermediate locking Manually Automatically Manually with intermediate locking Manually Automatically	
10	Type of spindle operation	Grade	Spindle operation			
		0 1 2 3 4	Lock or latch without follower Lock or latch for knob or sprung lever handle operation Lock or latch for unsprung lever handle operation Lock or latch for heavy duty unsprung lever handle operation Lock or latch as grade 3, but specified by the manufacturer			
11	Key identification requirement	Grade	Key identification			
		0 A B C D E F G H	No requirements Minimum 3 detaining elements Minimum 5 detaining elements Minimum 5 detaining elements, extended number of effective differs Minimum 6 detaining elements Minimum 6 detaining elements, extended number of effective differs Minimum 7 detaining elements Minimum 7 detaining elements, extended number of effective differs Minimum 8 detaining elements, extended number of effective differs			
	Dangerous substances	The materials used in this product shall not contain or release any dangerous substances in excess of the maximum levels specified in existing European material standards or any national regulations.				

## 10. Responsibility:

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

The declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Frank MacKenzie, Commercial Director

---

Raamsdonksveer, 25-07-2013

---

(Place & date of issue)



---

(Signature)

ASSA ABLOY Nederland B.V.  
Postbus 40, 4940 AA  
Meerval 3-5  
4941 SK Raamsdonksveer  
NETHERLANDS

Tel. + 31 (0)88 639 46 00  
Fax + 31 (0)88 639 46 75  
[www.assaabloy.nl](http://www.assaabloy.nl)

ASSA ABLOY is the  
global leader in door  
opening solutions,  
dedicated to  
satisfying  
end-user needs for  
security, safety and  
convenience.

[www.assaabloy.com](http://www.assaabloy.com)