



Thank you for purchasing this Croydex product. Please follow the fixing and care instructions to ensure your Stainless Steel Wire Storage product is fitted safely and retains its high quality finish.
Please retain this leaflet for future reference.

This instruction leaflet applies to the following Stainless Steel Wire storage products:

QM391941 STAINLESS STEEL SOAP DISH
QM390941 STAINLESS STEEL CORNER SOAP DISH
QM390641 STAINLESS STEEL COSMETIC BASKET
QM395941 STAINLESS STEEL CORNER BASKET
QM390841 STAINLESS STEEL SMALL TWO TIER CORNER BASKET
QM390241 STAINLESS STEEL MEDIUM TWO TIER CORNER BASKET
QM393841 STAINLESS STEEL LARGE TWO TIER CORNER BASKET
QM392841 STAINLESS STEEL 3 TIER CORNER BASKET
QM390541 STAINLESS STEEL 2 TIER COSMETIC BASKET

Fixing Pack Contents

Fixing Screws x 2
Wall Plugs x 2

Only use the fixings supplied.

Tools Required

Drill; 6mm masonry drill bit (6mm ceramic drill bit optional); Cross head screwdriver; Pencil; Spirit level.

KEEP DIY TOOLS OUT OF THE REACH OF CHILDREN

Home Safety Advice

Always take care when using an electric drill, particularly in the bathroom. Always check for hidden cables and pipe work before drilling and take extreme care if there is any water in the working area.

It is advisable to use a residual current circuit breaker (RCCB).

Always wear suitable eye protection when drilling.

If the product is to be fitted on a ceramic tiled wall, a ceramic drill bit should be used. Always ensure that the drill hole passes through the central tiled area rather than through the grouted area. To prevent damage to the tile, mask the area around the hole with tape before drilling.

Do not strike the product with hard or sharp objects.

Fitting Instructions

1. Select position of the product on the wall and mark through the fixing holes, ensuring that where applicable, the product is level.
2. Remove the product. Using a 6mm masonry drill, drill the holes in the marked positions to a depth of 30mm. If drilling through tiles, please pre-drill using a ceramic drill bit. Insert the wall plugs to the surface of the wall. If fitting to a tiled surface, the wall plugs should be inserted below the surface of the tile to avoid cracking.
3. Insert the screw(s) through the holes on the product and screw into the wall plug(s). Do not over tighten as cracking of the tiles could occur.

Product Care

To retain the best quality finish, clean product regularly with a soft cloth and mild detergents. Do not use abrasive or chemical cleaners, as these will damage the product.

Please retain this leaflet for future reference.

Croydex Limited, Central Way, Andover, Hants, SP10 5AW, UK
Tel: +44 (0) 1264 365881 Fax: +44 (0) 1264 356437
Website: www.croydex.com E-mail: info@croydex.co.uk.

WMA 059 R02