


# System-36 PLUS

Lorient's new range of System-36 PLUS glazing gaskets combines advanced technology with enhanced performance and features.

## Specification


- Fire resistance provided for 30 minute applications and 60 minute applications with approved glass types.\*
- Entire range is successfully tested for fire in accordance with BS 476: Pt.22: 1987 (Approved Document B).
- System-36/6 PLUS has been successfully tested to BS EN 1634-1: 2008 (Approved Document B).
- Flexible enough to be fitted to curved corners and circular vision panels.
- A sodium silicate liner is required for flaxboard substrates below 500kg/m<sup>3</sup> density.
- Each size variant features a unique colour on the spine for easier identification.
- Supplied coiled in a box so it's easily dispensed and cut to length, avoiding wastage in off-cuts.
- Suitable for use with a range of standard fixing beads.
- Suits different thicknesses of glass from 5mm to 23mm.
- \*Glass types: Please refer to Certifire certificate CF5060 for the full range of glass types.
- The product range is approved on the basis of the design appraisal against TS25.
- Standard profile lengths:
  - System-36/6 PLUS: 60 metre coil
  - System-36/7 PLUS: 60 metre coil
  - System-36/10 PLUS: 30 metre coil
  - System-36/15 PLUS: 30 metre coil
  - System-36/23 PLUS: 25 metre coil
- Standard finishes: Black.

System-36/6 PLUS




LG1512 PLUS

System-36/7 PLUS




LG1513 PLUS

System-36/10 PLUS




LG1717 PLUS

System-36/15 PLUS



LG2022 PLUS

System-36/23 PLUS



LG2229 PLUS



System-36/6 PLUS shown here

## Fitting instructions

Fitting is completely clean and dry. No sealant, adhesive tape or wet adhesive is required. Please consult the separate fitting instructions.

Please refer to our Technical Services team on **+44 (0)1626 834252** for further details.